



EASY TO MAINTAIN,

EASY TO FIX ...

... solid beech wood, hardwax oil floors

Pollmeier hardwax oil solid wood floors have a warm and natural radiance. They provide a highly wear-resistant surface that out-performs traditional oils used in floor finishing (e.g. boiled linseed oil) because of the combination of unique oils and wax.

Active households and lifestyles, including active kids and pets, will leave their marks on a floor. Nothing changes that. However, a hardwax oil floor, unlike other types of floor finishes or floor seals, allows an isolated section or area of the floor that has been subjected to excessive wear and tear to be repaired without totally re-doing the entire floor. With the Pollmeier repair kits, a floor owner can make repairs himself.

A Pollmeier solid wood floor, with a hardwax oil finish, is already treated and only requires an initial application with Osmo Liquid Wax Cleaner 3029 once installed. The floor can then be walked on immediately.



Hardwax-oiled surface

Varnished surface

Antique surface



IDEAL FOR A BUSY BUSINESS ENVIRONMENT



Stain resistant surfaces.



Naturally well maintained with Wash & Care ...



... and Liquid Wax Cleaner.

Whether in an office, restaurant, or exhibition hall – hardwax oil solid wood floors show their practical nature in business environments. The robust and resistant surfaces are less susceptible to being stained. Red wine, fruit juice and coffee spills do not leave stains even if not cleaned up promptly.

The ease of maintenance and upkeep make it ideal in places where traditionally wood floors were not recommended. Greater traffic in a given area simply means a more frequent preventative maintenance schedule of the floor.


Just follow the care and repair instructions and you will enjoy your solid wood floor for decades to come.

- The floor should regularly be cleaned with a damp mop or cloth. We recommend Osmo Wash & Care 8016; this cleaning agent was especially developed to meet the needs of an oil-wax surface.
- Twice a year (in residential use) we also recommend use of the Osmo Liquid Wax Cleaner 3029; this penetrates the oil and cleans the floors thoroughly.
- Depending on the intensity of use, the floor will need to be re-oiled. A change in the degree of gloss (appearance of footpaths) in higher traffic areas will indicate a need to re-oil the floor. The application of Osmo Hardwax-Oil 3054 after a thorough cleaning of the floor will rejuvenate the product.

Spot Repairs

Limited, do-it-yourself repairs can be easily made with the Pollmeier Repair Kit, by following the instructions in the Kit carefully. Saving you time and money on professional repair.

1. Sand out the spot you want to repair with a sanding sponge, grain size 180. Smooth the roughness of the bordering area with sandpaper, grain size 400.
2. Then apply the stain with a cloth, and dry it with a hair blower for about 2 minutes. Wipe the stained surface with a damp cloth and check the color tone. If the color is too light, the process must be repeated until the color tone matches the rest of the floor.
3. Apply Osmo Hardwax-Oil 3054 with a cloth onto the stained area and let dry for 12 hours. Avoid the area and rope it off from foot traffic.
4. After drying, apply Osmo Hardwax-Oil 3054 with a cloth a second time. If the results are not satisfactory, the process can be repeated. After twelve hours of drying, the floor can be walked on again.



POLLMEIER Leimholz GmbH
P.O. BOX 1260
D-33384 Rietberg
Rüschfeld 131
D-33397 Rietberg
Phone: +49 52 44 92 05-0
Fax: +49 52 44 92 05-66
e-mail: rietberg@pollmeier.com
www.pollmeier-flooring.com

US Sales Office
POLLMEIER Inc.
10200 SW Greenburg Rd., Suite 450
Portland, OR 97223
Phone: 503-452-5800
Fax: 503-452-5801
toll free: 866-432-0699
e-mail: flooring@pollmeier.com

Warranty disclaimer

No warranty exists with respect to Pollmeier's wood products, except for manufacturing defects. Pollmeier offers a limited warranty for its finish and does not offer a warranty for its hardwax-oil finish. Pollmeier warrants that its finish will be free from defects in material or manufacture. Pollmeier warrants its floor finish for 25 years under normal residential traffic conditions and 3 years under light commercial conditions, as described in Pollmeier's website. Pollmeier's warranty is applicable only to the original owner of its prefinished wood products. Pollmeier's warranty is limited to providing the original owner with repair, refinish, or replacement of the finish, at Pollmeier's sole discretion. For further information and up to date information regarding Pollmeier's warranty disclaimers, exclusions, installation instructions and requirements, and conditions, please visit www.pollmeier-flooring.com